


# RUGGED RUBBER KEYBOARD WITH PC KEYCAPS CATALOGUE

Rugged Keyboards and Mice Expert



深圳市键特电子有限公司  
东莞市键特电子有限公司  
KEY TECHNOLOGY CHINA LIMITED



Wechat: Keytechnology  
Email: sales01@key-tek.cn, sales05@key-tek.cn  
Telephone: +86-755-89230460, +86-755-89253893  
Webpage: www.rugged-key.com, www.rugged-system.com  
Head Office Add: B702, Building 1, Tian'an Cyber Park, HuangGe North Rd, Long Gang District, ShenZhen, P.R. China. Zip Code: 518172  
Factory Add: Floor 7, Building S8, Fenggang Tianan Cyber Park, No. 208 Fenggang Section, Dongshen Road, Fenggang Town, DongGuan City, Guang Dong Province, P.R. China. Zip Code: 523703  
Beijing Office Add: 1205, Floor 12, Building 7, No. 26 Chengtong Street, Shijingshan District, Beijing, P.R. China. Zip Code: 100043





# Company Profile

Established in 2006, Key Technology China Limited is an ISO9001-2015 and GJB9001C-2017 registered enterprise engaged in research, development, sale and service of all kinds of rugged keyboards/pointing devices for harsh environments covering industrial/military/marine/medical/coal mine/oil and gas/transportation/aerospace/public access/food and beverage/vehicle etc. applications. We have excellent and experienced teams who focus on product development & design, quality control and company running. Dedicated to strict quality control and thoughtful customer service, our experienced staff are always available to provide ideal solutions to customers. Ranging from our off-the-shelf products to customized one, we can always deliver you a satisfying solution! Besides, our products have obtained many certificates/testing reports including but not limit to CE, RoHS, FCC, ESD, REACH, GJB151A-1997, GJB150A-2009, GJB151B-2013, MIL-STD-461G-EMC-EMI-EMS-ESD, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, salt spray, temperature shock, rain, dust, fungus, solar radiation etc.), IEC60945-2002, IP67, IP68, Medical, Explosive-proof as well as patent certificates.

## Advantages of this series of products

1. Fully sealed semi-rugged dynamic waterproof patented technology
2. Solve the problem of heavy tactile feeling of silicone rubber keyboards
3. Solve the defects of regular silicone rubber keyboards and membrane scissor switch keyboards that are not vandal proof or resistant to prying or scratch
4. Perform well in dynamic waterproof/dust and sandstrom-proof, solve the defects of membrane scissiors switch keyboards and reinforced Chiclet keyboards that are not resistant to sandstorm
5. NO MOQ
6. Ultra thin standard semi-rugged version and fully rugged version optional
7. Keyboard and casing are sealed and ruggedized, easy for maintenance
8. Others

## Disadvantages of this series of products

1. Light tactile feeling but possible to have uneven actuation of every key
2. Non-vandalproof, when the side of keys is pressed or squeezed vigorously, there will be risk of broken sloping sidewall
3. When pressing the side or four corners of keys, the four corners and sides of keys cannot fall at the same time due to its internal structure, and might be tilt
4. Processing technology and procedures are complicated and with high cost
5. Others

## ★ Feature and Reliability ★

EMC SPEC	MIL-STD-461G (EMC, EMI, EMS, ESD)
01	CE101 25Hz - 10kHz Conducted Emissions, Audio Frequency Currents, Power leads
02	CE102 10kHz -10MHz Conducted Emissions, Radio Frequency Potentials, Power leads
03	CS101 25Hz - 150kHz Conducted Susceptibility, Power Leads
04	CS106 Conducted Susceptibility, Transients, Power Leads
05	CS112 Electrostatic Discharge Susceptibility
06	CS114 4kHz -400MHz Conducted Susceptibility, Bulk Cable injection
07	CS115 Conducted Susceptibility, Bulk Cable injection, Impulse Excitation
08	CS116 10kHz - 100MHz Conducted Susceptibility, Damped Sinusoidal Transients, Cables and Power Leads
09	RE101 25Hz -100kHz Radiated Emissions, Magnetic Field
1 0	RE102 10kHz - 18GHz Radiated Emissions, Electric Field
1 1	RS101 25HZ - 100kHz Radiated Susceptibility, Magnetic Field
1 2	RS103 10kHz - 40GHz Radiated Susceptibility, Electric Field

Environmental Adaptability	MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, fungus etc.)
01	Low Pressure (57kPa - 106kPa)
02	High Temperature (+75 ℃ )
03	Low Temperature (-40 ℃ )
04	Temperature Shock (-55 ℃ to +75 ℃ )
05	Rain Test (Wind velocity: no less than 18m/s, test duration: 3h)
06	Humidity (-30 ℃ to +60 ℃ , 95%RH)
07	Fungus (Test period: 28 days (672h))
08	Salt Spray (Test period: 96h, IEC60512-6)
09	Low Frequency Vibration
1 0	Dust Test (10.6g/m <sup>3</sup> ±7g/m <sup>3</sup> )
1 1	Vibration (Frequence: 0-2000Hz, Displacement: 1mm, Acceleration:70m/s <sup>2</sup> )
1 2	Shock (40g, 11ms)
1 3	Drop Test (Drop height: 122cm)

**Designed to meet the critical military standards in these 10 aspects:**  
Reliability, Safety, Maintainability, Testability, Supportability, Environmental adaptability, Stability, Compatibility, Consistency, and Continuity.



Part Number: K-TEK-M263-FN-BL-FC-KC+TP85-DML+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, 12 function keys (F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	81 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.35KG
Dimension:	Keyboard: 276.0mm x 110.3mm (L x W) TouchPad: 86.0mm x 61.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M290-FN-MS-KC-DM

### Feature

IP65 fully sealed and durable embedded ultra thin rugged silicone rubber matrix keyboard with PC keycaps, 12 function keys (F1, F2, ... F12) on top line for easy operation. The keyboard surface adopts ultra rugged P+R technology (PC keycaps + Rubber), utilizing reinforced special membrane switch key technology with key stroke (1.20mm) for extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. Ultra-thin aluminum reinforcement bottom plate for panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the 10 critical standards: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

### Mechanical Data

Keys:	87keys
Key Travel::	1.20±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.40KG
Dimension:	284.7mm x 126.8mm (Front Panel)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≈30mA
Connect Interface:	Dot matrix
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP65 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-20°C ~ +55°C
Storage Temperature:	-30°C ~ +65°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M290-134-FN-BL-FC-KC-DM

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, 12 function keys (F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.) and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.35KG
Dimension:	87.0mm x 106.0mm(L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	Dot matrix
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M290-134-FN-BL-FC-KC-DM+TP85-DML+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.),and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 + 2 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.40KG
Dimension:	Keyboard: 290.0mm x 134.3mm(L x W) TouchPad: 85.0mm x 60.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	Dot matrix
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M275TP-FN-BL-FC-KC-ML

### Feature

IP67 fully sealed and durable embedded ultra thin rugged military keyboard, with sealed & ruggedized tough touchpad for fast and accurate cursor position, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology. With 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid misoperation or typing error. Adjustable white backlight included, top panel mounting solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	92 keys (including 2 mouse buttons)
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.43KG
Dimension:	283.0mm x 177.7mm(L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.

### Optional Configuration

### Part Number

### Remark



K-TEK-M275TP-FN-BL-KC-ANA-151B

MIL-STD-461G-EMC-EMI-EMS-ESD standard



K-TEK-M275TP-FN-BL-KC-ANA-151B-AL

With aluminum alloy backplate



K-TEK-M275TP-FN-BL-FC-KC-FDT USB interface, mountable flat desktop with VESA holes



K-TEK-M275TP-FN-BL-FC-KC-FDT-WF

2.4G wireless, mountable flat desktop with VESA holes



Part Number: K-TEK-M275TP-FN-BL-KC-ANA-151B

### Feature

IP67 fully sealed and durable embedded ultra thin rugged military keyboard ,with sealed &ruggedized tough touchpad with 400 DPI resolution for fast and accurate cursor position,12 function keys (F1 ,F2 ,...F12)are on top line for easy operation,with combination numbers on letter keys for full keyboard functionality.Keyboard surface uses ultra rugged P+R technology (PC keycaps +Rubber), and utilizes carbon-on-gold key switch technology,with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise. There will be no key value missing ,no stuck key during keyboard operation ,with durable coating &anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment.**FN +CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid misoperation or typing error,adjustable white backlight and top panel mounting solution.Designed to meet **MIL-STD-461G-EMC-EMI-EMS-ESD and MIL-STD-810 H** (high and low wide temperature ,low pressure,humidity,vibration ,shock, temperature shock,rain ,salt mist , dust ,fungus ,solar radiation etc.),as well as the critical military standards in these 10 aspects: reliability,safety,maintainability, testability,supportability, environmental adaptability,stability,compatibility,consistency,and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	92 keys (including 2 mouse buttons)
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.65KG
Dimension:	283.0mm x 177.7mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-461G (EMC, EMI, EMS, ESD) and MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.)	
Protection Level:	IP67
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M275TP-FN-BL-KC-ANA-151B-AL

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard with semi-rugged aluminum backplate, with sealed & ruggedized tough touchpad with 400 DPI resolution for fast and accurate cursor position ,12 function keys (F1 ,F2 ,... F12)are on top line for easy operation,with combination numbers on letter keys for full keyboard functionality.Keyboard surface uses ultra rugged P+R technology (PC keycaps +Rubber),and carbon-on-gold key switch technology,with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise. There will be no key value missing , no stuck key during keyboard operation,with durable coating &anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment.**FN +CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid misoperation or typing error,adjustable white backlight and top panel mounting solution.Designed to meet **MIL-STD-461G-EMC-EMI-EMS-ESD and MIL-STD-810H** (high and low wide temperature ,low pressure,humidity,vibration ,shock,temperature shock, rain ,salt mist ,dust ,fungus,solar radiation etc.),as well as the critical military standards in these 10 aspects:reliability,safety, maintainability,testability,supportability,environmental adaptability, stability,compatibility,consistency,and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	92 keys (including 2 mouse buttons)
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.65KG
Dimension:	283.0mm x 177.7mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-461G (EMC, EMI, EMS, ESD) and MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.)	
Protection Level:	IP67
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M275TP-FN-BL-FC-KC-FDT

### Feature

IP68 fully sealed and durable rugged keyboard, with fully sealed waterproof reinforced wide temperature touchpad for fast and accurate cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology. With 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid misoperation or typing error. Adjustable white backlight included, VESA mountable super flat desk top version with robust ABS polycarbonate case. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	92 keys (including 2 mouse buttons)
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.65KG
Dimension:	297.58mm x 192.06mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP68
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M275TP-FN-BL-FC-KC-FDT-WF

### Feature

IP68 fully sealed and durable rugged 2.4G wireless keyboard, with fully sealed waterproof reinforced wide temperature touchpad for fast and accurate cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology. With 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid misoperation or typing error. Adjustable white backlight included, VESA mountable super flat desk top version with robust ABS polycarbonate case, wireless version. Designed to meet **MIL-STD-810H** (high and low wide working temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	92 keys (including 2 mouse buttons)
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.65KG
Dimension:	297.58mm x 192.06mm x 22.20mm (L x W x H)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	2.4G Wireless
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP68
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M280-FN-BL-FC-KC-DM

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin dot matrix Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.),and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.  
**Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data









Keys:	87 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.33KG
Dimension:	280.0mm x 97.6mm(L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	Dot matrix
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTRR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.

Optional Configuration	Part Number	Remark
	K-TEK-M280-FN-BL-FC-KC-ML-EP	With rugged aluminum alloy frame
	K-TEK-M280-FN-BL-FC-KC-DM-EP	Dot matrix, with rugged aluminum alloy frame
	K-TEK-M280-FN-BL-FC-KC-ML	USB interface, rubber keyboard with PC keycap
	K-TEK-M280-FN-BL-FC-KC+TP85-DML+2K-FC	Keyboard with touchpad
	K-TEK-M280-FN-BL-FC-KC-EP+TP85-DML+2K	With touchpad and rugged aluminum alloy frame
	K-TEK-M280-FN-BL-FC-KC+TP65-DML+2K-PC	Keyboard with touchpad
	K-TEK-M280-FN-BL-FC-KC-ANA-151B+TP85+2K	With touchpad and MIL-STD-461G-EMC-EMI-EMS-ESD standard
	K-TEK-M280-FN-BL-FC-KC-ANA-151B+TP65+2K	With touchpad and MIL-STD-461G-EMC-EMI-EMS-ESD standard



Part Number: K-TEK-M280-FN-BL-FC-KC-ANA-151B+TP85+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged military keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. FN + Clean combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet MIL-STD-461G-EMC-EMI-EMS-ESD and MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, sand and dust, fungus, solar radiation etc.), as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	86 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.60KG
Dimension:	Keyboard: 280.0mm x 97.3mm (L x W) TouchPad: 86.0mm x 61.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-461G (EMC, EMI, EMS, ESD) and MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.)	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M280-FN-BL-FC-KG+TP65-DML+2K-PC

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. FN + CLEAN combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and MIL-STD-461G-EMC-EMI-EMS-ESD (optional), as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	Keyboard: 280.0mm x 97.3mm(L x W) TouchPad: 66.0mm x 50.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M280-FN-BL-FC-KC-DM-EP

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin dot matrix Flexible Printed Circuit, back plate made of reinforced aluminum alloy, and the front panel is equipped with an aluminum alloy frame to reinforce and prevent keyboard deformation, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	294.8mm x 112.1mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	Dot matrix
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M280-FN-BL-FC-KC-ML

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810F** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.),and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	280.0mm x 97.3mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M280-FN-BL-FC-KC-ML-EP

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard with built-in ultra-thin Flexible Printed Circuit, and the front panel is equipped with an aluminum alloy frame to reinforce and prevent keyboard deformation. 12 function keys (F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, drop, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity. **Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data

Keys:	86 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	294.8mm x 112.1mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M280-FN-BL-FC-KC+TP65-DML+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, 12 function keys (F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity. **Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data

Keys:	86 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.20KG
Dimension:	Keyboard: 280.0mm x 97.3mm (L x W) Touchpad: 66.0mm x 50.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M280-FN-BL-FC-KC-TP85-DML+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	Keyboard:280.0mm x 97.6mm(L x W); TouchPad: 85.0mm x 60.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M280-FN-BL-FC-KC-ANA-151B+TP65+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged military keyboard ,with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate ,external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position ,12 function keys (F1 ,F2 ,...F12)are on top line for easy operation ,with combination numbers on letter keys for full keyboard functionality.Keyboard surface uses ultra rugged P+R technology (PC keycaps +Rubber),and adopts carbon contact and FPC carbon-on-gold key switch technology,with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise ,there will be no key value missing ,no stuck key during the keyboard operation ,with durable coating &anti -microbial keyboard surface withstand most chemicals and liquids under harsh environment.**FN +CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing.Adjustable white backlight included ,panel mount solution.Designed to meet **MIL-STD-461G-EMCEMI-EMS-ESD and MIL-STD-810H** (high and low wide temperature ,low pressure,humidity,vibration ,shock,temperature shock, drop ,rain,s alt mist ,sand and dust ,fungus ,solar radiation etc.),as well as the critical military standards in these 10 aspects: reliability,safety, maintainability,testability,supportability,environmental adaptability, stability,compatibility,consistency,and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.60KG
Dimension:	Keyboard: 280.0mm x 97.3mm (L x W) TouchPad: 61.0mm x 45.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-461G (EMC, EMI, EMS, ESD) and MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315KP-FN-BL-FC-KC-DM

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin dot matrix Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, with independent numeric keypad on the right side of keyboard and 12 function keys (F1, F2, ... F12) on top line for easy operation. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.35KG
Dimension:	315.0mm x 108.0mm(L x W)


### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	Dot matrix
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.

Optional Configuration	Part Number	Remark
	K-TEK-M315KP-FN-BL-FC-KC-DM-EP	With rugged aluminum alloy frame
	K-TEK-M315KP-FN-BL-FC-KC-ML	USB interface, rubber keyboard with PC keycap
	K-TEK-M315KP-FN-BL-FC-KC+TP85-DML+2K-PC	Keyboard with touchpad
	K-TEK-M315KP-FN-BL-FC-KC+TP85-DML+2K-FC	Keyboard with touchpad
	K-TEK-M315KP-FN-BL-FC-KC+TP65-DML+2K	Keyboard with touchpad
	K-TEK-M315KP-FN-BL-FC-KC-EP+TP85-DML+2K	With touchpad and rugged aluminum alloy frame
	K-TEK-M315KP-FN-BL-FC-KC-ANA-151B+TP85+2K	With touchpad and MIL-STD-461G-EMC-EMI-EMS-ESD standard



Part Number: K-TEK-M315KP-FN-BL-FC-KC-DM-EP

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin dot matrix Flexible Printed Circuit, back plate made of reinforced aluminum alloy, and the front panel is equipped with an aluminum alloy frame to reinforce and prevent keyboard deformation, with independent numeric keypad on the right side of keyboard and 12 function keys(F1, F2, ... F12) on top line for easy operation. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity. **Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data

Keys:	102 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	330.6mm x 123.6mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	Dot matrix
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315KP-FN-BL-FC-KC-ML

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, with independent numeric keypad on the right side of keyboard and 12 function keys (F1, F2, ... F12) on top line for easy operation. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity. **Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data

Keys:	102 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	315.0mm x 108.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315KP-FN-BL-FC-KC-ANA-151B+TP85+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard with Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad and 2 mouse keys for fast cursor position, with independent numeric keypad on the right side of keyboard and 12 function keys (F1, F2, ... F12) on top line for easy operation. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and utilizes carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-461G-EMC-EMI-EMS-ESD and MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.),, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	315.0mm x 108.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-461G (EMC, EMI, EMS, ESD) and MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.)	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315KP-FN-BL-FC-KC-EP+TP85-DML+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit, with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, and independent numeric keypad on the right side of keyboard and 12 function keys (F1, F2, ... F12) on top line for easy operation. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, reinforced aluminum alloy back plate with mounting holes for rear panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.50KG
Dimension:	Keyboard: 330.6mm x 123.6mm (L x W) Touchpad: 85.0mm x 60.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315KP-FN-BL-FC-KC+TP85-DML+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, with independent numeric keypad on the right side of keyboard and 12 function keys(F1, F2, ... F12) on top line for easy operation. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology,with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.),and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.38KG
Dimension:	Keyboard: 315.0mm x 108.0mm (L x W); Touchpad: 85.0mm x 60.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315KP-FN-BL-FC-KC+TP85-DML+2K-PC

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced stainless steel back plate, and sealed waterproof reinforced wide-temperature external touchpad with 400DPI for fast cursor position, with independent numeric keypad on the right side of keyboard and 12 function keys (F1, F2, ... F12) on top line for easy operation. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology,with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, sand & dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈0.50KG
Dimension:	Keyboard: 315.0mm x 108.0mm (L x W); Touchpad: 86.0mm x 61.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315KP-FN-BL-FC-KC+TP65-DML+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, with independent numeric keypad on the right side of keyboard and 12 function keys(F1, F2, ... F12) on top line for easy operation. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.35KG
Dimension:	Keyboard: 315.0mm x 108.0mm (L x W) Touchpad: 66.0mm x 50.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M300-108-FN-BL-FC-ML+M73TP

### Feature

IP67 fully sealed and durable embedded ultra thin rugged silicone rubber keyboard, with built-in Flexible Printed Circuit and semi-reinforced ultra-thin aluminum alloy plate, external with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, with 12 function keys (F1, F2, ... F12) on top line for easy operation. The keyboard surface adopts silicone rubber material and carbon contact + FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, sand and dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys+ 2 mouse buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 3.50KG
Dimension:	300.0mm x 107.7mm (Front Panel) Touchpad: 76.0mm x 73.0mm (front panel)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	30mA when backlight is off, 300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-45°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315TP-FN-BL-FC-KC-ML

### Feature

IP67 fully sealed and durable embedded ultra thin rugged military keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, with fully sealed waterproof reinforced wide temperature touchpad for fast and accurate cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.),and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.  
**Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data



Keys:	87 keys (including 2 mouse buttons)
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.36KG
Dimension:	315.0mm x 108.0mm(L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, meet MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.

Optional Configuration	Part Number	Remark
	K-TEK-M315TP-FN-BL-KC-ANA-151B	MIL-STD-461G-EMC-EMI-EMS-ESD standard
	K-TEK-M315TP-FN-BL-FC-KC-ML-EP	With rugged aluminum alloy frame



Part Number: K-TEK-M315TP-FN-BL-KC-ANA-151B

### Feature

IP67 fully sealed and durable embedded rugged military keyboard with fully sealed waterproof reinforced wide temperature touchpad with 400DPI resolution for fast and accurate cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and carbon-on-gold key switch technology with 1.50mm ±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no missing key, no stuck key, no repeat key value output during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-461G-EMC-EMI-EMS-ESD and MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, sand and dust, fungus, solar radiation etc.), as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys (including 2 mouse buttons)
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.37KG
Dimension:	315.0mm x 108.0mm(L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-461G (EMC, EMI, EMS, ESD) and MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.)	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M315TP-FN-BL-FC-KC-ML-EP

### Feature

IP67 fully sealed and durable embedded ultra thin rugged military keyboard, with built-in ultra-thin Flexible Printed Circuit, reinforced aluminum alloy back plate, and the front panel is equipped with aluminum alloy frame to reinforce and prevent keyboard deformation, with fully sealed waterproof reinforced wide temperature touchpad for fast and accurate cursor position, 12 function keys(F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	87 keys (including 2 mouse buttons)
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.38KG
Dimension:	TBA

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M340KP-FN-BL-FC-KC-ML

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible PrintedCircuit and semi-reinforced ultra-thin stainless steel back plate (ultra full rugged version with aluminum backplate available), 12 function keys (F1, F2, ... F12) are on top line for easy operation, with numeric keys on right side. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.  
**Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data




Keys:	102 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.35KG
Dimension:	340.0mm x 110.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.

Optional Configuration	Part Number	Remark
	K-TEK-M340KP-FN-BL-FC-KC-DM	Dot matrix, rubber keyboard with PC keycap
	K-TEK-M340KP-FN-BL-FC-KC-ANA-151B+TP85+2K	With touchpad and MIL-STD-461G-EMC-EMI-EMS-ESD standard
	K-TEK-M340KP-FN-BL-FC-KC+TP85-DML+2K-FC	Keyboard with touchpad



Part Number: K-TEK-M340KP-FN-BL-FC-KC-DM

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin dot matrix Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate, 12 function keys (F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.30KG
Dimension:	340.0mm x 110.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	Dot matrix
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M340KP-FN-BL-FC-KC-ANA-151B+TP85+2K

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate (ultra full rugged version with aluminum backplate available), with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, 12 function keys (F1, F2, ... F12) are on top line for easy operation, with numeric keys on right side. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Fully sealed and dynamic waterproof, dust and sandstorm-proof patented structure. Designed to meet **MIL-STD-461G-EMC-EMI-EMS-ESD and MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust and sandstorm, fungus, solar radiation etc.), as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.50KG
Dimension:	Keyboard: 340.0mm x 110.0mm (L x W) TouchPad: 85.0mm x 60.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-461G (EMC, EMI, EMS, ESD) and MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M340KP-FN-BL-FC-KC+TP85-DML+2K-FC

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and semi-reinforced ultra-thin stainless steel back plate (ultra full rugged version with aluminum backplate available), with fully sealed waterproof and reinforced wide-temperature touchpad for fast cursor position, 12 function keys (F1, F2, ... F12) are on top line for easy operation, with numeric keys on right side. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. **FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, drop, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	102 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 0.50KG
Dimension:	Keyboard: 340.0mm x 110.0mm (L x W) TouchPad: 85.0mm x 60.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67 (front panel)
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M445-OTB-FN-FC-KC-BL-ML-BT

### Feature

IP67 fully sealed and durable embedded ultra thin rugged keyboard, with built-in ultra-thin Flexible Printed Circuit and full-rugged stainless steel housing, integrated with a conventional mouse with middle wheel, left/right buttons as well as one 34mm optical trackball mouse at 800DPI resolution for fast cursor moving, 12 function keys (F1, F2, ... F12) are on top line for easy operation, with combination numbers on letter keys for full keyboard functionality. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key, no repeat key value during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment.

**FN + CLEAN** combination keys for easy cleaning without taking the keyboard away from PC to avoid mis-operation or mis-typing. Adjustable white backlight included, panel mount solution. Designed to meet **MIL-STD-810F** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.), and **MIL-STD-461G-EMC-EMI-EMS-ESD (optional)**, as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity.

Patented keyboard (Patent number: 202420937267.2)

### Mechanical Data

Keys:	86 keys
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.5N±0.2N
Gross Weight:	≈ 2.50KG
Dimension:	445.0mm x 172.0mm x 72.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	50mA when backlight is off, 300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android.

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IP67
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-45°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M342-BL-KC-NV-EMC

### Feature

IPX6 fully sealed and durable embedded rugged radar keyboard, designed to meet IEC60945-2002 EMC and environmental adaptability test. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. High quality durable CNC aluminum alloy rugged front plate and back plate, adjustable white backlight included, built in top panel mounted solution with 6 x M4 sinking holes, with aviation plug or USB port. Power button/7 rotary encoder buttons on top/20 function keys on left and right side to be customized and programmed by users. Which is designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, dust, salt mist, fungus, solar radiation etc.), as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity; **MIL-STD-461G (EMC, EMI, EMS, ESD) optional**.  
**Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data

Keys:	61 keys for keyboard part + 20 function keys + 7 rotary encoder buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 3.0KG
Dimension:	342.0mm x 185.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IPX6
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.



Part Number: K-TEK-M450-OTB-RS-BL-KC-NV-EMC

### Feature

IPX6 fully sealed and durable embedded rugged radar keyboard designed to meet IEC60945-2002 EMC and environmental adaptability test, as well as integrated with 34mm optical trackball module with 500CPI for fast and accurate cursor position with extreme smooth operation without any noise, the entire trackball can be directly removed from the front, facilitating installation, maintenance, and after-sales service. Keyboard surface uses ultra rugged P+R technology (PC keycaps + Rubber), and adopts carbon contact and FPC carbon-on-gold key switch technology, with 1.50mm±0.10mm key travel with extremely good tactile feeling for fast and accurate data input without any noise, there will be no key value missing, no stuck key during the keyboard operation, with durable coating & anti-microbial keyboard surface withstand most chemicals and liquids under harsh environment. High quality durable CNC aluminum alloy rugged front plate and back plate, adjustable white backlight included, built in top panel mounted solution with 6 x M4 sinking holes, with aviation plug or USB port. Power button/7 rotary encoder buttons on top/20 function keys on left and right side to be customized and programmed by users. Which is designed to meet **MIL-STD-810H** (high and low wide temperature, low pressure, humidity, vibration, shock, temperature shock, rain, dust, salt mist, fungus, solar radiation etc.), as well as the critical military standards in these 10 aspects: reliability, safety, maintainability, testability, supportability, environmental adaptability, stability, compatibility, consistency, and continuity; **MIL-STD-461G (EMC, EMI, EMS, ESD) optional**.  
**Patented keyboard (Patent number: 202420937267.2)**

### Mechanical Data

Keys:	61 keys for keyboard part + 20 function keys + 7 rotary encoder buttons
Key Travel::	1.50±0.10mm
Key Lifespan:	>5 million actuations
Actuation Force:	1.2N±0.2N
Gross Weight:	≈ 3.5KG
Dimension:	450.0mm x 185.0mm (L x W)

### Electrical Data

Supply Voltage:	DC +5V±5%
Working Current:	≤30mA when backlight is off, ≤300mA with backlight on
Connect Interface:	USB
OS:	All Windows, Linux, Unix, Mac OSX, Vxworks, Android, (U-cos--To be confirmed).

### Reliability

RoHS compliant, CE and FCC certified, MIL-STD-810H (high and low wide temperature, low pressure, humidity, vibration, shock,temperature shock, rain, salt mist, dust, fungus, solar radiation etc.).	
Protection Level:	IPX6
MTBF:	>20000H
MTTR:	<30min
Operating Temperature:	-40°C ~ +75°C
Storage Temperature:	-50°C ~ +85°C
APPLICATION:	Vehicle, aerospace, naval, defense, maritime, Radar, console, portable rugged laptop, notebook, UAV ground station, GCS etc.